PENGUIN®
LADDERS + SCAFFOLDING

FIBREGLASS WORK PLATFORM LADDER

- FRP Stiles with aluminium steps and platform
- Wide 100mm depth step for safe access
- 900mm guardrail with safety chain and 360 coverage protecting user
- FWPL 4 to 6, Standard model with back end FRP stability bar at base
- FWPL 7 to 12 Double ended FRP stability bars at base for greater stability
- Aluminium platform with slip resistance and toeplate for additional safety
- Rungs crimped onto stile for robustness and strength
- Handrails in built for assisted access
- **Optional: Safety barrier and/or wheels and/or outrigger**







FRP STABILITY BAR



PENGUIN®
LADDERS + SCAFFOLDING

ELECTRICALLY NON-CONDUCTIVE

FIBREGLASS WORK PLATFORM LADDER
LOAD CAPACITY: 175 KG


ITEM CODE	STEPS + PLATFORM	PLATFORM HEIGHT		FREESTANDING HEIGHT		WORKING HEIGHT *		APPROXIMATE WEIGHT
		METRES	FEET	METRES	FEET	METRES	FEET	KILOGRAMS
FWPL 4	3+1	1	3'3"	1.9	6'3"	3	9'10"	17.7
FWPL 5	4+1	1.25	4'1"	2.2	7'3"	3.25	10'7"	19.5
FWPL 6	5+1	1.5	4'11"	2.4	7'10"	3.5	11'5"	21.8
FWPL 7	6+1	1.75	5'8"	2.7	8'10"	3.75	12'3"	25.1
FWPL 8	7+1	2	6'7"	2.9	9'6"	4	13'1"	27
FWPL 9	8+1	2.25	7'5"	3.2	10'6"	4.25	13'11"	29.2
FWPL 10	9+1	2.5	8'2"	3.4	11'2"	4.5	14'9"	31.2
FWPL 12	11+1	3	9'10"	3.9	12'9"	5	16'5"	37.8

TECHNICAL FEATURES ARE INDICATIVE AND CAN BE MODIFIED WITHOUT PRIOR NOTICE


ADDITIONAL OPTIONS



SPRING WHEEL*1



FIXED WHEEL



OUTRIGGER*2

* 1 Spring wheel only up to 7 steps (6+1)
* 2 Outrigger is only applicable from 10 steps and up

Ideal for: Stores & Factories Warehouses Electrical Commisioning